



Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle One, Two, or Three Compartment Sinks, model _____, with 2"-wide "Euro-Style" edging on front and sides. Unit constructed of heavy gauge type 430 stainless steel top and sink bowls. Sinks to be deep-drawn, seamless and have all corners covered. Drainboards, when required, shall be "V" creased for positive drainage. 9½" high backsplash with 1" upturn and tile edge. Legs to be 1½" O.D. galvanized tubing, with front-to-back crossbracing, and 1" high impact plastic adjustable bullet feet.



**FEATURING
2"-WIDE
EURO-STYLE
EDGING**

Options / Accessories

- | | |
|--|--|
| <input type="checkbox"/> Stainless steel legs | <input type="checkbox"/> Faucets |
| <input type="checkbox"/> Stainless steel bullet feet | <input type="checkbox"/> Sink covers |
| <input type="checkbox"/> White metal bullet feet | <input type="checkbox"/> Waste outlet |
| <input type="checkbox"/> Lever drains | <input type="checkbox"/> Sink kits |
| <input type="checkbox"/> Twist handle drains | <input type="checkbox"/> Overflow hole |
| <input type="checkbox"/> Twist drain brackets | |

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration or fabrication needs, contact our **SpecFAB®** Division.

Phone: 302-653-3000 • Fax: 302-653-3091 • e-mail: specfab@eaglegrp.com

Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

412 Series Sinks

MODELS:

- | | | |
|---------------------------------------|---------------------------------------|---------------------------------------|
| <input type="checkbox"/> 412-16-* | <input type="checkbox"/> 412-16-*-24L | <input type="checkbox"/> 412-24-*-18R |
| <input type="checkbox"/> 412-16-*-18 | <input type="checkbox"/> 412-16-*-24R | <input type="checkbox"/> 412-24-*-24 |
| <input type="checkbox"/> 412-16-*-18L | <input type="checkbox"/> 412-24-* | <input type="checkbox"/> 412-24-*-24L |
| <input type="checkbox"/> 412-16-*-18R | <input type="checkbox"/> 412-24-*-18 | <input type="checkbox"/> 412-24-*-24R |
| <input type="checkbox"/> 412-16-*-24 | <input type="checkbox"/> 412-24-*-18L | |

* See charts on back page for full model numbers.

Materials

- Sink bowls: Heavy gauge type 430 stainless steel.
- Top: Drainboards, backsplash and euro-style edging are heavy gauge type 430 stainless steel.
- Legs: 1½" (41mm)-diameter heavy-gauge galvanized tubing with plated 12-gauge gussets and high-impact corrosion resistant fully adjustable bullet feet.
- Crossbracing, running front-to-back, is 1" (25mm)-diameter heavy-gauge galvanized tubing.

Design and Construction Features

- All bowls have deep-drawn one-piece seamless construction, using state-of-the-art hydraulic presses.
- All sink bowls have a generous radius—3" (76mm) minimum—and are rectangular for maximum capacity.
- 10½" (267mm) water level — 13½" (343mm) flood level.
- 44½" (1130mm) overall height.
- Entire assembly is fuse-welded and planished, providing a one-piece seamless sink unit.
- Drainboards, when provided, are integrally welded.
- 9½" (241mm)-high full length standard backsplash features 1" (25mm) upturn and tile edge for easy installation and feathering to wall/splash surface.
- Welded areas are blended to match adjacent surfaces with continuity of satin finish.
- Leg gussets are welded to a die-cut heavy gauge reinforcing plate.
- Leg gusset assemblies welded adjacent to sink bowls, providing increased stability and maximum weight support.

Mechanical:

- Water supply is ½" (13mm) IPS for hot and cold lines.
- Faucet holes are 1½" (29mm), punched on 8" (203mm) centers; two sets of faucet holes are punched where indicated on chart (back page).
- Basket-type waste drains included fit sink bowls' 3½" (89mm) opening and feature 1½" (38mm) outlet.

Certifications / Approvals



AUTOQUOTES






Profit from the Eagle Advantage®

Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

412 Series Sinks


Sinks with One Compartment



TOP VIEW OF ONE-COMPARTMENT SINKS

model #	bowl dimensions				drainboard			overall dimensions				weight	
	width		length		quantity	length		width		length		lbs.	kg
	in.	mm	in.	mm			in.	mm	in.	mm	in.	mm	
412-16-1	20"	508	16"	406	0	-	-	27½"	699	23¼"	591	40	18.1
412-16-1-18R or L	20"	508	16"	406	1	18"	457	27½"	699	38⅞"	987	59	26.8
412-16-1-18	20"	508	16"	406	2	18"	457	27½"	699	54½"	1384	78	35.4
412-16-1-24R or L	20"	508	16"	406	1	24"	610	27½"	699	44⅞"	1140	65	29.5
412-16-1-24	20"	508	16"	406	2	24"	610	27½"	699	66½"	1689	90	40.8
412-24-1	24"	610	24"	610	0	-	-	31¾"	807	31½"	800	60	27.2
412-24-1-18R or L	24"	610	24"	610	1	18"	457	31¾"	807	46¾"	1188	79	35.8
412-24-1-18	24"	610	24"	610	2	18"	457	31¾"	807	62"	1575	98	44.5
412-24-1-24R or L	24"	610	24"	610	1	24"	610	31¾"	807	52½"	1340	85	38.6
412-24-1-24	24"	610	24"	610	2	24"	610	31¾"	807	74"	1880	110	49.9


Sinks with Two Compartments



TOP VIEW OF TWO-COMPARTMENT SINKS

model #	bowl dimensions				drainboard			overall dimensions				weight	
	width		length		quantity	length		width		length		lbs.	kg
	in.	mm	in.	mm			in.	mm	in.	mm	in.	mm	
412-16-2	20"	508	16"	406	0	-	-	27½"	699	41"	1041	64	29.0
412-16-2-18R or L	20"	508	16"	406	1	18"	457	27½"	699	56⅝"	1438	83	37.6
412-16-2-18	20"	508	16"	406	2	18"	457	27½"	699	72¼"	1835	102	46.3
412-16-2-24R or L	20"	508	16"	406	1	24"	610	27½"	699	62⅝"	1591	89	40.4
412-16-2-24	20"	508	16"	406	2	24"	610	27½"	699	84¼"	2140	114	51.7
412-24-2	24"	610	24"	610	0	-	-	31¾"	807	57½"	1461	90	40.8
412-24-2-18R or L	24"	610	24"	610	1	18"	457	31¾"	807	72¾"	1847	109	49.4
412-24-2-18	24"	610	24"	610	2	18"	457	31¾"	807	88"	2235	128	58.1
412-24-2-24R or L	24"	610	24"	610	1	24"	610	31¾"	807	78¾"	2000	115	52.2
412-24-2-24	24"	610	24"	610	2	24"	610	31¾"	807	100"	2540	140	63.5

Sinks with Three Compartments



TOP VIEW OF THREE-COMPARTMENT SINKS

model #	bowl dimensions				drainboard			overall dimensions				weight	
	width		length		quantity	length		width		length		lbs.	kg
	in.	mm	in.	mm			in.	mm	in.	mm	in.	mm	
412-16-3	20"	508	16"	406	0	-	-	27½"	699	58¾"	1492	85	38.6
412-16-3-18R or L	20"	508	16"	406	1	18"	457	27½"	699	74⅝"	1895	104	47.2
412-16-3-18	20"	508	16"	406	2	18"	457	27½"	699	90"	2286	123	55.8
412-16-3-24R or L	20"	508	16"	406	1	24"	610	27½"	699	80⅝"	2042	110	49.9
412-16-3-24	20"	508	16"	406	2	24"	610	27½"	699	102"	2591	135	61.2
412-24-3 *	24"	610	24"	610	0	-	-	31¾"	807	83½"	2121	125	56.7
412-24-3-18R or L *	24"	610	24"	610	1	18"	457	31¾"	807	98¾"	2508	144	65.3
412-24-3-18 *	24"	610	24"	610	2	18"	457	31¾"	807	114"	2896	163	73.9
412-24-3-24R or L *	24"	610	24"	610	1	24"	610	31¾"	807	104¾"	2661	150	68.0
412-24-3-24 *	24"	610	24"	610	2	24"	610	31¾"	807	126"	3200	175	79.4

* Features two sets of faucet holes.

EAGLE GROUP
 100 Industrial Boulevard, Clayton, DE 19938-8903 USA
 Phone: 302-653-3000 • Fax: 302-653-2065
 www.eaglegrp.com

Foodservice Division: Phone 800-441-8440
 MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A.
 ©2012 by Eagle Group

Rev. 06/12

Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.