


Project:	AIA#
ltem:	
Location:	SIS#
Approved:	

3 Year Parts/Labor Warranty **Additional 2 Year Compressor Warranty**

REACH-IN BLAST CHILLER

BF124AP Solid Door Self-Contained Blast Chiller

MODEL: BF124AP



- Soft and hard, timed or core probe shock freezing
- · Automatic recognition of core probe
- Multi point sensor temperature display button
- · Core probe heater button
- HACCP alarm display button
- · Pre-cooling cycle button
- Adjustable evaporator fan speed button
- · Timed manual defrost button
- USB data recorder/interface
- · Infinity mode program with adjustable set point
- Automatic conservation mode at end of cycle
- On board recipe book with 68 pre-set programs
- 99 Free memory positions for custom programs
- LCD illuminated temperature display
- Unit comes standard with twelve (12) wire rod tray slides
- · Real time clock
- One, high precision heated multi sensor probe
- Stainless steel feet

OPTIONS & ACCESSORIES

- UV sterilization lamp (must be added at time of order)
- Single sensor probes (up to 4 possible)
- · Change door swing
- Casters with brakes
- Rs 485 connection for external monitoring system

REFRIGERATION SYSTEM

- · Self-contained refrigeration system uses R404 refrigerant to comply with all environmental concerns
- Evaporator fitted with a high flow rate fan insures maximum cooling efficiency
- Indirect air flow assures highest product quality
- · Manual defrosting with door open on a timed cycle
- Blast chilling (194°F to 37°F in 90 minutes) or shock freezing (194°F to 0°F in 240 minutes) cycles













MODEL	BF124AP
EXTERNAL DIMENSIONAL DATA	
Width Overall (in)	33.46"
Depth Overall (in)	33.46"
Height Overall (in)	70.87"
Number of Doors	1
Width, Door Opening (in)	62.99"
PERFORMANCE DATA	
Sheet Pan Capacity (18" x 26") (pans not included)	12
Steam Table Pan Capacity (12" x 20") (pans not included)	12
Chilling Capacity In 90 Min	100 lbs
Freezing Capacity In 240 Min	70 lbs
Climate Class	5
ELECTRICAL DATA	
Cabinet Voltage	208-240/60/3
Total Amperes	9.0
NEMA Plug	15-20P
REFRIGERATION DATA	
Condensing Unit Size, HP	2.0
Refrigerant	R404
Capacity (BTU/Hr) (113°F/-13°F)	10,318
Heat Rejection (W) (14°F/95°F)	10,342
Refrigerant Amount (lbs)	3.53
WEIGHT DATA	
Gross Weight - Crated	602 lbs
Height - Crated	78"
Width - Crated	38"
Depth - Crated	37"

Self-Contained Blast Chiller/Shock Reach-In Freezer Model: BF124AP

