

|          |           |
|----------|-----------|
| Project: | Quantity: |
| Model #: | Approval: |

For Commercial Use Only

## C-2RE 54" Double Solid Door Reach-In Refrigerator



### FEATURES

- Stainless steel interior and exterior
- Aluminum back
- Refrigeration system keeps food at safe temperatures
- Self-closing doors with 90 degree stay-open feature
- Locks and keys included
- Adjustable heavy-duty PVC coated shelves
- Recessed door handle
- Electronic control system
- Preinstalled heavy-duty casters with brakes
- Removable installation board
- Hydro-Carbon R290 refrigerant

This Coldline stainless steel reach-in commercial refrigerator is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- cETLus Listed
  - ETL Sanitation Listed
- Conforms to UL & NSF Standards



USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

## TECHNICAL DATA

### DIMENSIONS

|                      |                        |
|----------------------|------------------------|
| Exterior Dimensions  | 54"W x 32.2"D x 81.5"H |
| Interior Dimensions  | 49.4"W x 27"D x 60.3"H |
| Packaging Dimensions | 56.3"W x 34"D x 84.5"H |
| Net Volume           | 47 cu. ft.             |
| Unit Weight          | 448 lb.                |
| Shipping Weight      | 530 lb.                |

### ELECTRICAL

|                   |            |
|-------------------|------------|
| Voltage           | 115        |
| Hertz             | 60         |
| Phase             | 1          |
| Amps              | 3.8        |
| Plug Type         | NEMA 5-15P |
| Power Cord Length | 96"        |

### COOLING

|                        |              |
|------------------------|--------------|
| Temperature Range      | 33°F to 41°F |
| Refrigerant            | R290         |
| Max. Ambient Temp      | 90°F         |
| Defrosting             | Automatic    |
| Temperature Controller | Digital      |
| Horsepower             | 1/4+         |

### CONSTRUCTION

|                         |                                   |
|-------------------------|-----------------------------------|
| Exterior Material       | 430 Stainless Steel               |
| Interior Material       | 304 Stainless Steel               |
| Insulation Material     | Foamed-in-Place Polyurethane      |
| Shelf Size              | 6 Qty: 20.9"W x 25.2"D            |
| Shelf Material          | Epoxy Coated Wire                 |
| Shelf Load Capacity     | 120 lb.                           |
| Adjustable Shelf        | Yes                               |
| Interior Light          | L.E.D                             |
| Mobility Wheels/Casters | (4) Qty: 2 with brakes, 2 without |

## TECHNICAL DRAWING

MODEL: C-2RE



NEMA 5-15P

