



Advance Features Include:

- ✓ Standard Display Models: CK-12, CK-30, CK-60
- ✓ Pole Display Models: CK-P12, CK-P30, CK-P60
- ✓ High Resolution: 1/6000 NTEP Approved class III
- ✓ Large LCD displays with 6 digit pricing and weight.
- ✓ AC Adapter included
- ✓ 4 Direct PLU keys programmable with tare and unit price!
- ✓ Built-In rechargeable battery: Over 100 hours of continuous use!



CK-Series Feature Guide

- ❑ 1/6000 Resolution, Legal for Trade Approval #03-011
- ❑ Stainless Steel platter and ABS plastic sub-platter
- ❑ Ultra Quick-Response Weight display
- ❑ Portable design: easily used in any location
- ❑ Tough high quality UV-sealed keypad
- ❑ Compact medium-sized footprint design
- ❑ Capacities: 12 x 0.002 lb / 30 x 0.005 lb / 60 x 0.01 lb
- ❑ Pole display models: CK-P12, CK-P30, & CK-P60
- ❑ User-friendly PLU programming
- ❑ Quick operation keypad for high throughput
- ❑ Function keys: 4 PLUs, Save, Tare, and Zero
- ❑ External AC adapter with long power cord



Technical Specifications

Models:	CK-12 & CK-P12	CK-30 & CK-P30	CK-60 & CK-P60
Capacity and Graduation:	12 x 0.002 lb	30 x 0.005 lb	60 x 0.01 lb
Maximum Tare:	12 lb	30 lb	60 lb
NTEP Certificate Number:	Approved 1/6000 resolution, Legal for Trade, CC #03-011		
A/D Conversion Rate:	50 Updates / second		
Direct PLU Keys:	4 Direct PLU keys which can be programmed with Tares and Unit Prices		
Liquid Crystal Displays (LCD):	Weight: 6 Digits, 999.999 max		
	Unit Price: 6 Digits, 9999.99 max		
	Total Price: 6 Digits, 9999.99 max		
Platter Size:	Width: 300 mm / 11.8"		
	Length: 225 mm / 8.9"		
Accreditation:	NTEP Class III, OIML, CE, ISO 9002		
Product Dimensions:	CK-12, CK-30, CK-60	CK-P12, CK-P30, CK-P60	
	Width: 320 mm / 12.6"	Width: 320 mm / 12.6"	
	Length: 340 mm / 13.4"	Length: 340 mm / 13.4"	
	Height: 125 mm / 4.5"	Height: 575 mm / 22.6"	
AC Adapter Specifications:	AC Input: 120 Volts AC @ 60 Hz, DC Output: 9 Volts DC, 800mA, Positive Tip		
Battery Specifications:	100 hours without backlight / 48 hours with backlight (Continuous use.)		
Power Consumption & Fuse Rating:	Approximately 10 Watts / Fuse: 250 Volts, 1.5 Amp, 20 mm		

Options

<input type="checkbox"/> Foreign Power Adapter: 220 Volts AC @ 50 Hz	<input type="checkbox"/> Fish Tray Optional Platter
<input type="checkbox"/> Cigarette Lighter Car Adapter	<input type="checkbox"/> Wet-Proof Protective Overlay

Acom America Inc.
 404 Paulding Ave.
 Northvale, New Jersey 07647
 Tel: (201) 750-9900
 Fax: (201) 750-7100
 www.easyweighscales.com



Distributed by:

*NOTE: Specifications are subject to change without notice.