

Project:	AIA#
Item:	
Location:	SIS#
Approved:	

# DRAFT BEER EQUIPMENT-DIRECT DRAW DISPENSER

MODEL: **DD68HC-1-S** 

DD68HC Solid Door Dual Towers, One Single & One Dual Faucets **Hydrocarbon Series** 



3 Year Parts/Labor Warranty **Additional 4 Year Compressor Warranty** 

#### **CABINET CONSTRUCTION**

- · Exterior stainless steel with galvanized steel back
- Top is made from heavy-duty stainless steel including drip tray
- Interior is galvanized steel on walls and ceiling, reinforced floor and doorsills are heavy-duty stainless steel
- Full electronic control
- Dual towers, one (1) with single faucet and one (1) with dual faucets
- 3-in-1 Draft solution uses a single stainless-steel tap to serve different beverages, such as wine, beer, and coffee (or other non-alcoholic beverages) through silver-lined, anti-microbial tubing that is 100% effective against the top 4 beverage spoiling bacteria
- 3" Stainless steel insulated dispensing tower
- Drain tube located at bottom front of cooler for connection to floor drain
- Door locks
- Self-closing doors with 120° stay-open feature
- · Magnetic gaskets provide positive door seal
- Field reversible doors (hinge kit not included)
- Compressor available on left or right, specify at time of unit order

#### **OPTIONS & ACCESSORIES**

- Club top
- · Stainless steel interior lining
- Stainless steel back
- · Glass door
- Shelves
- Shelf clips
- Custom tower hole location
- Drip tray location option
- Wine models
- Faucet locks
- Glass rinser
- Right or left hinged door
- 2"- 3" Casters or 6" black legs
- 1- 6 Tap tower
- 2, 3 & 4 way manifolds
- Dual tap placement option
- No draft/hole cover option
- Remote option\* (see note on back on page)

## **REFRIGERATION SYSTEM**

- Refrigeration system uses R290 refrigerant to comply with all environmental concerns
- Automatic, non-electric defrost
- · Epoxy coated evaporator coil
- Maintains product temperatures between 36°F and 38°F

















MODEL	DD68HC-1-S	
EXTERNAL DIMENSIONAL DATA		
Width Overall	69"	
Depth Overall	29"	
Height Overall (floor to top of tap)	52 ½"	
Number of Doors	2	
Depth with Door Open 90°	50 ½"	
Door Openings (in)	21" x 30"	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	25.93	
Internal Width Overall (in)	56 ½"	
Internal Depth Overall (in)	23 1/8"	
Internal Height Overall (in)	27 1⁄4"	
Number of 1/2 Kegs	3	
ELECTRICAL DATA		
Full Load Amperes	5.5	
REFRIGERATION DATA		
Horsepower	1/3	
Capacity (BTU/Hr)	2392	
Heat Rejection (BTU/Hr)	3588	
Charge (lbs/grams)	0.2535/115	
SHIPPING DATA		
Gross Weight - Crated	380 lbs	
Height - Crated	45"	
Width - Crated	72"	
Depth - Crated	32"	

\*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.



### **Bar Equipment-Direct Draw Beer Dispenser** Model: DD68HC-1-S



#### **ELECTRICAL CONNECTION**



Unit pre-wired at factory and include 8' long cord and plug set.













