

Project:	AIA#
ltem:	
Location:	SIS#
Approved:	

DRAFT BEER EQUIPMENT-DIRECT DRAW DISPENSER

DD94HC Solid Door Twelve Tap Tower Hydrocarbon Series

MODEL: DD94HC-1-B-12T



3 Year Parts/Labor Warranty
Additional 4 Year Compressor Warranty

CABINET CONSTRUCTION

- Exterior features durable black painted steel with galvanized steel back
- Top and drip tray are heavy-duty stainless steel
- Interior is galvanized steel on walls and ceiling, reinforced floor is heavy-duty stainless steel
- Full electronic control
- Twelve tap tower
- 3-in-1 Draft solution uses a single stainless-steel tap to serve different beverages, such as wine, beer, and coffee (or other non-alcoholic beverages) through silver-lined, anti-microbial tubing that is 100% effective against the top 4 beverage spoiling bacteria
- Drain tube located at bottom front of cooler for connection to floor drain
- 4" Insulated dispensing tower
- Door locks
- Self-closing doors with 120° stay-open feature
- Magnetic gaskets provide positive door seal
- Field reversible doors (hinge kit not included)
- Compressor available on left or right, specify at time of unit order

OPTIONS & ACCESSORIES

- · Stainless steel interior lining
- Stainless steel back
- Glass door
- Shelves
- Shelf clips
- Wine models
- Faucet locks
- Glass rinser
- Right or left hinged door
- 2"- 3" Casters or 6" black legs
- No draft/hole cover option
- Remote option* (see note on back on page)

REFRIGERATION SYSTEM

- Refrigeration system uses R290 refrigerant to comply with all environmental concerns
- Automatic, non-electric defrost
- Epoxy coated evaporator coil
- Maintains product temperatures between 36°F and 38°F

















MODEL	DD94HC-1-B-12T	
EXTERNAL DIMENSIONAL DATA		
Width Overall	95"	
Depth Overall	29"	
Height Overall with Tap	53 ½"	
Number of Doors	3	
Depth with Door Open 90°	50 ½"	
Door Opening (in)	21" x 30"	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	37.82	
Internal Width Overall (in)	82 ¼"	
Internal Depth Overall (in)	23 1/8"	
Internal Height Overall (in)	27 1⁄4"	
Number of 1/2 Kegs	5	
ELECTRICAL DATA		
Full Load Amperes	5.5	
REFRIGERATION DATA		
Horsepower	1/3	
Capacity (BTU/Hr)	2392	
Heat Rejection (BTU/Hr)	3588	
Charge (lbs/grams)	0.2535/115	
SHIPPING DATA		
Gross Weight - Crated	532 lbs	
Height - Crated	58"	
Width - Crated	97"	
Depth - Crated	32"	

*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.



Bar Equipment-Direct Draw Beer Dispenser Model: DD94HC-1-B-12T



ELECTRICAL CONNECTION



Unit pre-wired at factory and include 8' long cord and plug set.













