## GRIDDLES











				DIMENSIONS (INCHES)		TEMPERATURES			
MODEL	VOLTAGE	POWER (W)	AMPS	WIDTH	DEPTH	HEIGHT	°C	°F	LBS
EGD-24	208/240 V	4200/5600W	20.2/23.4A	24"	21.7"	12.9"	65°-250°C	150°-480°F	92.92
EGD-36	208/240 V	6300/8400W	30/35A	36"	21.8"	12.9"	65°-250°C	150°-480°F	123.13

- ◆ EGD-24: Two independently controlled heat zones, 24"W x 16-1/2"D grilling surface
- ◆ EGD-36: Three independently controlled heat zones, 36"W x 16-1/2"D grilling surface
- Stainless steel body and catch tray
- ◆ Stainless steel side and rear backsplash for food containment
- ◆ Solid steel plate with a 1/2" thickness on both EGD-24 and EGD-36
- EGD-24 supplied with a plug and lead (NEMA L6-30P) for quick installation/connection
- Adjustable feet
- ◆ UL listed for compliance with UL-197
- ◆ NSF listed for compliance with NSF-4
- One year parts and labor warranty

ITEM	DESCRIPTION	UOM
<b>⊚</b> EGD-24	Electric Griddle, 24", 240 Volts, with Plug and Lead	Set
<b>⊚</b> EGD-36	Electric Griddle, 36", 240 Volts	Set
EHD-P12	Replacement Knob for EGD-24 & EGD-36	Each





Tel. 1.888.946.2652 Fax. 1.562.926.5678