



Sandwich Prep



PRODUCT HIGHLIGHTS

- Tecumseh compressor
- 5" Casters Standard
- Durable and Easy to Adjust
- Holds 36°F ~ 41°F
- Defrost Timer System
- ETL UL Certified
- Stainless steel front, top and sides
- Aluminum sides and top with stainless steel floor
- High-Density Polyurethane foam cell insulation (CFC Free)
- Self closing door
- Adjustable Epoxy Wire shelves



MODEL	WXDXH	DOORS	SHELF	VOLTS	H.P.	FOR 1/6 PAN	CU.FT	WEIGHT
LM27 S/C	27X32X45	1	1	115	1/4	9	7.7	134
LM27 R	27X32X45	1	1	115	-	9	9.7	110
LM36 S/C	36X32X45	1 1/2	1	115	1/4	12	12.2	176
LM36 R	36X32X45	2	2	115	-	12	14.9	145
LM48 S/C	48X32X45	1 1/2	1	115	1/3	18	16.2	208
LM48 R	48X32X45	2	2	115	-	18	19.9	170
LM60 S/C	60X32X45	1 1/2	1	115	1/3	24	20.3	228
LM60 R	60X32X45	2	2	115	-	24	25.8	187
LM72 S/C	72X32X45	2 1/2	3	115	1/3	30	26.2	285
LM72 R	72X32X45	3	3	115	-	30	29.9	250
LM84 S/C	84X32X45	2 1/2	3	115	1/3	30	30.3	350
LM84 R	84X32X45	3	3	115	-	30	35.7	295
LM96 S/C	96X32X45	3 1/2	3	115	1/2	36	36.2	400
LM96 R	96X32X45	4	4	115	-	36	49.8	345

Additional Features:

- Our defrost timer system keeps cooling systems separate from the evaporator. It doesn't ice up or inhibit the compressor, giving the unit outstanding performance and a longer life even in the most difficult environments.
- These models are designed to operate in an environment where temperature and humidity do not exceed 75°F and 65% relative humidity.

*S/C for the self contained models

*R for remote models