

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Pass Thru Half Glass Door Heated Cabinet

Pass-Thru PRO Series

Model: PRO-50-4H-G-PT

___ FEATURES & BENEFITS =__

■ Digital temperature control & monitor system

- Keep food products safe by maintaining constant temperatures.
- · Alarm beeps when doors are not sealed.
- Early warning alarm program detects issues before malfunction occurs.
- · Digital display allows for easy monitoring.
- · Sensitive touch display.

■ Ducted fan air distribution system

Maintains temperature within the food zone

On/Off switch

ON/OFF switch is located on control panel

All stainless steel cabinet construction

The PRO series model boasts a stainless steel interior and a 22 gauge stainless steel exterior (galvanized steel top, bottom). It guarantees the utmost in cleanliness and long product life. The PRO series model adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air PRO series uniquely provides stainless steel shelving.

■ LED interior lighting

Includes a U.S. patented dimming option, exclusively from Turbo Air. This feature reduces energy consumption by 3~5%.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- Half length glass doors with locks
- Self-closing doors with stay open feature at 120
- Heated cabinet holds 140°F ~ 180°F for the best in food preservation
- Lifetime guaranteed heavy duty hinges and handles














Model: PRO-50-4H-G-PT

ELECTRICAL DATA		
Voltage	208/115/60/1	
Plug Type	NEMA L14-20P	
Full Load Amperes	15	
Wattage (W)	3000	
Feed Wires with Ground	4	
Cord Length (ft.)	8	
DIMENSIONAL DATA		
# of Doors	8	
# of Racks Accepted	2	
Net Capacity (cu. ft.)	48.7	
Ext. Length Overall (in.)	513/4 (1314mm)	
Ext. Depth Overall (in.)*	361/4 (920mm)	
Ext. Height Overall (in.)†	78 (1982mm)	
Int. Length Overall (in.)	421/4 (1073mm)	
Int. Depth Overall (in.)	275/8(702mm)	
Int. Height Overall (in.)	58 _{3/4} (1493mm)	
# of Shelves	6	
Shelf Size (L x D) (in.)	223/4 x 263/8	
Net Weight (lbs.)	492	
Gross Weight (lbs.)	550	

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

WARRANTY: 3 Year Parts and Labor Warranty


STANDARD FEATURES

- Door locks standard
- · Standard 4" dia. swivel casters with locks on the front set
- Easy replaceable one piece magnetic door gaskets
- Solid and sturdy grille design
- ** Lead time applies. Please contact your sales representative for more details to order.


OPTIONAL ACCESSORIES

- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- 4.7" leveling seismic leg (1/2", 13 TPI): 30221M0500
- 6" stainless steel leg: 30221M0600
- Additional stainless steel shelf: (L, R) H50R901700
- Half door bun tray rack: TSP-2224 (each holds up to six 18"L x 26"D sheet pans)
- Tray slides kits: TS23-N1LR(#1), TS23-N1LR HALF, TS23-N4LR(#4), TS23-N4LR HALF, TS23-UNLR-H(Universal), TS23-UNLR-H HALF
- (1) Pair of #1 Tray Slides: H26R104460
- (1) Pair of Universal Tray Slides: H26R104470

PLAN VIEW



(unit: inch)



Ver 20210802

















■ Turbo Air: 800-627-0032 ■ GK: 800-500-3519 ■ Warranty: 800-381-7770 ■ AC: 888-900-1002

^{*} Depth does not include 2-1/2" for door handles.

[†] Height does not include 5" for caster height.