

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA #:	SIS #:	
CSI Section 11400		

# Sandwich & Cheese Display Cases

**Open Display** Merchandisers

## Patented Self-Cleaning Condenser



# Model: TOS-40NN-D-W(B)



# \_\_\_\_ FEATURES & BENEFITS \_\_\_\_

## Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

#### Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

## Exterior is white (black) with a mirror finish

#### Top shelf equipped

Top shelf is white (black) glass and frame is stainless steel, both with a mirror finish.

- High-density polyurethane insulation The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.
- Digital temperature controller
- Single pane glass is tempered for safety
- Stainless steel airflow grille
- Self-contained system, no plumbing required
- Bottom lit, LED interior lighting

Model	Load Line CU./FT.	HP	AMPS	Crated Weight (lbs.)	$L \ge D \ge H^{\star}$ (inches)
TOS-40NN-D-W(B)	1.83	1/3	8	572	401/4 x 353/8 x 40

Ver 20210629 Printed in U.S.A.

\* Height does not include 2-1/4" for caster height.

# Sandwich & Cheese Display Cases

# Model : TOS-40NN-D-W(B)

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	<b>NEMA 5-15P</b>			
Full Load Amperes	8			
Compressor HP	1/3			
Cord Length (ft.)	81/4			
Refrigerant	R-290			
DIMENSIONAL DATA				
Load Line Net Capacity (cu. ft.)	1.83			
Ext. Length Overall (in.)	401/4 (1022mm)			
Ext. Depth Overall (in.)	353/8 (900mm)			
Ext. Height Overall (in.)*	40 (1017mm)			
Int. Length Overall (in.)	353/8 (900mm)			
Int. Depth Overall (in.)	251/4 (641mm)			
Int. Height Overall (in.)	61/2 (164mm)			
Int. Height Load limit (in.)	31/2 (90mm)			
Top Shelf Size (L x D)(in.)	<b>27</b> 1/2 x 97/8			
Net Weight (lbs.)	385			
Gross Weight (lbs.)	572			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection. \* Height does not include 2-1/4" for caster height.

height does not include 2-1/4 for castel height.

## WARRANTY : <sup>2</sup> Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

## STANDARD FEATURES

• White and black color come standard


• 3" dia. swivel casters with locks on the rear set \*\*Extended lead time applies. Please contact your sales representative for more details to order.

#### Recommended operating conditions


TOS models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively. Keep the cycle air duct area clear of objects for optimal cooling.

## **PLAN VIEW**


(unit : inch)



TOP VIEW



FRONT VIEW



Ver.20210629

NATURALØ

Turbo air

- **Turbo Air** : 800-627-0032 **GK** : 800-500-3519
- Warranty : 800-381-7770 AC : 888-900-1002

Texaking

Continued product development may necessitate specification changes without notice.