

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Model: TST-60SD-08S-N-CL

Prep Table + Work Station - Clear Lid

Sandwich/Salad Prep Super Deluxe Series

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system

Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

■ Hvdrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Cold Bunker system

Our innovative forced air system allows cold air to flow all around the food pan area, covering not only underneath the pan, but also the front, top and the rear. This unique air flow creates a cold air-shield around the pan, which maintains the food temperature at under 41°F (NSF requirement) even when the lids are opened. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

Insulated pan cover

■ LED interior lighting & fan control

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior (ABS door liner) and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place high density, CFC free polyurethane insulation.

- 9-1/2" deep, 1/2" thick high-density Polyethylene cutting board included with convenient side rail
- Refrigerator holds 33°F ~ 39°F for the best in food preservation











Model	Swing Doors	CU./FT.	#of Shelves	#of Pans	HP	AMPS	Crated Weight (lbs.)	L x D [*] x H [†] (inches)
TST-60SD-08S-N-CL	2	19	2	8	1/5	8.9	312	601/4 x 30 x 37

(unit: inch)

Model: TST-60SD-08S-N-CL

Voltage 115/60/1 Plug Type NEMA 5-15P Full Load Amperes 8.9 Compressor HP 1/5 Feed Wires with Ground 3 Cord Length (ft.) 9 Refrigerant R-290 DIMENSIONAL DATA Ext. Length Overall (in.) 601/4 (1530mm) Ext. Depth Overall (in.)* 30 (763mm) Ext. Height Overall (in.)* 37 (940mm) # of Doors 2 # of Shelves 2 # of Pans 8 # of Hood 1 Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.) 27 x 17						
Plug Type NEMA 5-15P Full Load Amperes 8.9 Compressor HP 1/5 Feed Wires with Ground 3 Cord Length (ft.) 9 Refrigerant R-290 DIMENSIONAL DATA Ext. Length Overall (in.) 601/4 (1530mm) Ext. Depth Overall (in.)* 30 (763mm) Ext. Height Overall (in.)† 37 (940mm) # of Doors 2 # of Shelves 2 # of Pans 8 # of Hood 1 Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.) 27 x 17	ELECTRICAL DATA					
Full Load Amperes 8.9 Compressor HP 1/5 Feed Wires with Ground 3 Cord Length (ft.) 9 Refrigerant R-290 DIMENSIONAL DATA Ext. Length Overall (in.) 601/4 (1530mm) Ext. Depth Overall (in.)* 30 (763mm) Ext. Height Overall (in.) 7 # of Doors 2 # of Shelves 2 # of Pans 8 # of Hood 1 Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.) 27 x 17	Voltage	115/60/1				
Compressor HP 1/5 Feed Wires with Ground 3 Cord Length (ft.) 9 Refrigerant R-290 DIMENSIONAL DATA Ext. Length Overall (in.) 601/4 (1530mm) Ext. Depth Overall (in.)* 30 (763mm) Ext. Height Overall (in.)† 37 (940mm) # of Doors 2 # of Shelves 2 # of Pans 8 # of Hood 1 Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.)	Plug Type	NEMA 5-15P				
Feed Wires with Ground 3 Cord Length (ft.) 9 Refrigerant R-290 DIMENSIONAL DATA Ext. Length Overall (in.) 601/4 (1530mm) Ext. Depth Overall (in.)* 30 (763mm) Ext. Height Overall (in.)† 37 (940mm) # of Doors 2 # of Shelves 2 # of Pans 8 # of Hood 1 Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.) 27 x 17	Full Load Amperes	8.9				
Cord Length (ft.) Refrigerant R-290 DIMENSIONAL DATA Ext. Length Overall (in.) Ext. Depth Overall (in.)* Stat. Height Overall (in.)† # of Doors # of Shelves # of Pans # of Hood Net Capacity (cu. ft.) Shelf Size (L x D) (in.) R-290 90 80 601/4 (1530mm) 30 (763mm) 37 (940mm) 37 (940mm) 4 of Doors 2 # of Pans 8 # of Hood 1 Net Capacity (cu. ft.) 19	Compressor HP	1/5				
Refrigerant R-290 DIMENSIONAL DATA Ext. Length Overall (in.) 601/4 (1530mm) Ext. Depth Overall (in.)* 30 (763mm) Ext. Height Overall (in.)† 37 (940mm) # of Doors 2 # of Shelves 2 # of Pans 8 # of Hood 1 Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.) 27 x 17	Feed Wires with Ground	3				
DIMENSIONAL DATA Ext. Length Overall (in.) 601/4 (1530mm) Ext. Depth Overall (in.)* 30 (763mm) Ext. Height Overall (in.)† 37 (940mm) # of Doors 2 # of Shelves 2 # of Pans 8 # of Hood 1 Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.) 27 x 17	Cord Length (ft.)	9				
Ext. Length Overall (in.) 601/4 (1530mm) Ext. Depth Overall (in.)* 30 (763mm) Ext. Height Overall (in.)† 37 (940mm) # of Doors 2 # of Shelves 2 # of Pans 8 # of Hood 1 Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.) 27 x 17	Refrigerant	R-290				
Ext. Depth Overall (in.)* 30 (763mm) Ext. Height Overall (in.)† 37 (940mm) # of Doors 2 # of Shelves 2 # of Pans 8 # of Hood 1 Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.) 27 x 17	DIMENSIONAL DATA					
Ext. Height Overall (in.) † 37 (940mm) # of Doors 2 # of Shelves 2 # of Pans 8 # of Hood 1 Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.) 27 x 17	Ext. Length Overall (in.)	601/4 (1530mm)				
# of Doors 2 # of Shelves 2 # of Pans 8 # of Hood 1 Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.) 27 x 17	Ext. Depth Overall (in.)*	30 (763mm)				
# of Shelves 2 # of Pans 8 # of Hood 1 Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.) 27 x 17	Ext. Height Overall (in.)†	37 (940mm)				
# of Pans 8 # of Hood 1 Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.) 27 x 17	# of Doors	2				
# of Hood 1 Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.) 27 x 17	# of Shelves	2				
Net Capacity (cu. ft.) 19 Shelf Size (L x D) (in.) 27 x 17	# of Pans	8				
Shelf Size (L x D) (in.) 27 x 17	# of Hood	1				
	Net Capacity (cu. ft.)	19				
Net Weight (lbs.) 280	Shelf Size (L x D) (in.)	27 x 17				
	Net Weight (lbs.)	280				
Gross Weight (lbs.) 312	Gross Weight (lbs.)	312				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

- * Depth does not include 1" for rear spacers.
- † Height does not include 5" for caster height.

■ WARRANTY: 3 Year Parts and Labor Warranty Additional 4 Year Warranty on Compressor


STANDARD FEATURES

- Anti-corrosion coated evaporator
- · Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Standard 1/6 size, 4" deep condiment pans included
- ** Lead time applies. Please contact your sales representative for more details to order.


OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, ½" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Additional stainless steel shelf: M607800100
- Removable food cover: RCT-28
- Single overshelf, stainless steel, 60-3/8" W: TSOS-5S
- Double overshelf, 18/304 stainless steel, 60-1/4" W: TSOS-5R
- Door lock: lead time applies. Please contact your sales representative for more details to order.

PLAN VIEW



TOP VIEW



SIDE VIEW

NATURAL Refrigerant











■ Turbo Air : 800-627-0032 ■ GK : 800-500-3519 ■ Warranty : 800-381-7770 ■ AC : 888-900-1002









